

# KOMPACT



**FLOOD AND RESTORATION • DRYING WALLS, PLASTER, CEILINGS,  
PAINTING • LAUNDRIES • VEHICLE STORAGE • STORAGE AREAS  
BASEMENTS/CELLARS • LABORATORIES • OFFICES**

# THE KOMPACT

With the demands for reliability and performance ever increasing, the Kompact brings together the ruggedness of the building dryer range and the high specification with adaptability of the professional range. Manufactured to Ebac's high quality standards the Kompact will withstand the toughest of environments.

## DESIGNED AND BUILT TO LAST

The Kompact has a tough Stoved Epoxy powder finish ensuring it meets the rigours of both the hire and restoration sectors as well as maintaining a high visual appearance. The large rear wheels allow easy transport on site.

## LOW TEMPERATURE OPERATION

A hot gas defrost system ensures quick and efficient clearing of ice from the coil allowing a minimum operating temperature of 3°C. The Kompact's intelligent temperature defrost control ensures the highest possible performance across broader operating temperatures.

## POWERFUL AND ECONOMICAL

The Kompact has the power to extract up to 20 litres of water in a single day, yet running costs are very low. The Kompact requires no installation, just position the unit where needed, plug in, switch on and leave it to get on with the job.

## APPLICATIONS

- Flood and restoration
- Drying walls, plaster, ceilings, painting
- Laundries
- Vehicle storage
- Storage areas
- Basements/cellars
- Laboratories
- Offices

## SPECIFICATION

Height	615mm
Width	508mm
Depth	488mm
Weight	37kg
Voltage	230V
Power	0.75KW
Supply Fuse Rating	13A
Recommended Generator Size	1.5KVA
Airflow	152m <sup>3</sup> /hr
Effective Volume	237m <sup>3</sup>
Refrigerant	R407C
Typical Running Cost	5p per hr
Typical Water Extraction	20lts per day
30°C / 80% RH	

## FEATURES

On/Off Control	✓
Carrying Handle	✓
Filter	✓
Electronic Defrost Timer	✓
Condensate Pump	✓
Hour Meter	✓
Large Rear Wheels	✓
Cable Tidy	✓
Quiet Operation	✓
Stoved Epoxy Finish	✓
Minimum Temp	3°C
Maximum Temp	35°C

